

Technical Data: ECO-888 Updated: 1/16/18



ECO-888

Premium Clear Strippable Adhesive

Clear, Strippable, Non-Staining Wallcovering Adhesive

Product Number(s): 18805, 18801

Base: Starch

Product Information

General Properties: The second part of a two-part system. Must be used in conjunction with ECO-988 Pigmented Wallpaper Primer for desired results.

- Strippable
- Machinable
- Maximum tack
- Use with ECO-988 Primer with for best results
- LEED compliant
- NSF/ANSI 342 compliant

Recommended Uses: For all weights of wallcoverings.

Compatible Coatings: For desired results, first apply ECO-988 Pigmented

Wallpaper Primer

Mildew-Resistant: All Roman products contain biocides for in-can

preservation

Specification Data

Coverage: Up to approx. 330 square feet per gallon

VOC (actual/regulatory): 0% / 0 g/L as calculated per EPA Method 24

Storage: Avoid freezing; keep in cool, dry place

Drying Time: Drying time will vary depending on the temperature, ventilation,

and humidity of the room.



Technical Data: ECO-888 Updated: 1/16/18

Application Instructions

Surface Preparation: Surface must be free from mold, mildew, grease and other residues; dry, smooth and structurally sound. Refer to the www.epa.gov website for guidelines on cleaning and/or removing mold and mildew. Allow walls to dry, preferably below 2% moisture. Priming required with ECO-988 Pigmented Wallpaper Primer. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. Apply an even coat of adhesive at recommended spread rate using a pasting machine or roller. Do not overspread. Avoid contact with the surface of embossed, textured or delicate wallcoverings. Book according to the wallcovering manufacturer's instructions.

Clean-Up: Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.