

ROYSONS CORPORATION TEST REPORT

SCOPE OF WORK

ASTM E648-19A STANDARD TEST METHOD FOR CRITICAL RADIANT FLUX OF FLOOR-COVERING SYSTEMS USING A RADIANT HEAT ENERGY SOURCE ON WALLWRAP; CAVIAR

PROJECT NUMBER

104318997SAT-001

TEST DATE


05/14/2020

ISSUE DATE

05/18/2020

PAGES

8



TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020

REPORT ISSUED TO

ROYSONS CORPORATION

40 Vanderhoof Avenue

Rockaway, NJ 07866

SECTION 1

SCOPE

Intertek Building & Construction (B&C) was contracted by ROYSONS CORPORATION, 40 Vanderhoof Avenue, Rockaway, NJ 07866 to perform testing in accordance with ASTM E648-19A Standard Test Method for Critical Radiant Flux of Floor-Covering Systems using a Radiant Heat Energy Source, on their WALLWRAP; CAVIAR. Results obtained are tested values and were secured by using the designated test method. Testing was conducted at the Intertek B&C test facility in Elmendorf, TX. This report does not constitute performance certification of this product nor an opinion or endorsement by this laboratory.

SECTION 2

TEST METHOD

The specimen was evaluated in accordance with the following:

ASTM E648-19A, *Standard Test Method for Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source*

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

For INTERTEK B&C:

COMPLETED BY:	Theodore Salazar
TITLE:	Technician 3
SIGNATURE:	
DATE:	05/18/2020

REVIEWED BY:	Servando Romo
TITLE:	Project Engineer
SIGNATURE:	
DATE:	05/26/2020

TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020

SECTION 3

TEST SPECIMEN DESCRIPTION

SAMPLE ID	CAVIAR
DESCRIPTION	WALLWRAP
SPECIMEN PREPARATION	Specimen was sent by client in a sheet. Specimen was then cut to the dimensions required by the standard (41in x 9in to fit into the test frame) by Intertek.
RECEIVED DATE	04/30/2020 (Samples received in good condition)
INTERTEK SAMPLE TRACKER NUMBER	SAT2004301612-001
SAMPLE COND.	69.8±5.4°F and 50±5% relative humidity
ENVIRONMENTAL COND.	73°F and 63-65% r.h.

SECTION 4

LIST OF OBSERVERS

NAME	COMPANY
Theodore Salazar	Intertek B&C

SECTION 5

TEST OVERVIEW & PROCEDURE

This procedure provides a way of measuring critical radiant flux (the level of incident radiant heat energy on a floor covering system at the most distant flame-out point, reported as W/cm²) of horizontally mounted floor-covering systems exposed to a flaming ignition source while being exposed to radiant heat energy from a panel with approximately a 30° angle from the horizontal. The radiant flux ranges from 1.09 W/cm² at the 100 mm mark to 0.13 W/cm² at the 900 mm mark.

At least three specimens shall be tested. The specimens are conditioned at 69.8 ± 5.4°F and a relative humidity of 50 ± 5 % for a minimum of 48 hours. Following the ASTM E648-19A calibration procedures, the first specimen was loaded into the test chamber. After a 5 minute pre-heat time, the pilot flame was placed into contact with the specimen at the 0 mm mark. This pilot flame is to remain in contact with the specimen for 5 minutes, then removed. If the specimen does not propagate flame during the 5 minute pilot flame contact, then the test is terminated. For specimens that do propagate flame, the test is continued until the flame goes out. The distance to the farthest flame-out point is noted, which is then used to determine the

TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020

critical radiant flux, based on a radiant heat energy flux profile curve of the apparatus obtained during calibration.

SECTION 6
TEST RESULTS

Specimen	1	2	3
Maximum Distance (mm)	80*	40*	60*
Time to Max. Distance (min.)	10:00	10:00	10:00
Critical Radiant Flux (W/cm ²)	>1.09*	>1.09*	>1.09*
Time to All Flame Out (min.)	10:00	10:00	10:00

*Data below 100mm is not available. (Radiant Flux at 100mm =1.09 W/cm sq.)
It is not part of the test standard procedure to record radiant flux values below 100mm.

Run No.	Smoking	Discolored	Ignition
1	0:46	3:29	5:06
2	0:53	4:32	5:02
3	0:51	2:40	5:02

Average Critical Radiant Flux
(W/cm²) = N/A

Standard deviation = N/A

Coefficient of variation = N/A

TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020

SECTION 7**REQUIREMENTS FOR CLASSES**

ASTM E648 does not have a pass/fail criteria. In most cases the codes that require this testing will indicate criteria for the critical radiant heat flux as categorized by Class I or Class II. The requirements for these classes will depend on the code that is applicable for the product and/or installation.

For example, NFPA 101 Life Safety Code (2015 edition) states that:

10.2.7.3* Interior floor finishes shall be classified in accordance with 10.2.7.4, based on test results from NFPA 253, Standard Method of Test for Critical Radiant Flux of Floor Covering Systems Using a Radiant Heat Energy Source, or ASTM E 648, Standard Test Method for Critical Radiant Flux of Floor Covering Systems Using a Radiant Heat Energy Source.

10.2.7.4.1 Class I Interior Floor Finish. Class I interior floor finish shall have a critical radiant flux of not less than 0.45 W/cm², as determined by the test described in 10.2.7.3.

10.2.7.4.2 Class II Interior Floor Finish. Class II interior floor finish shall have a critical radiant flux of not less than 0.22 W/cm², but less than 0.45 W/cm², as determined by the test described in 10.2.7.3.

The requirements for the above mentioned classes will depend on the code that is applicable for the product and/or installation.

TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020

SECTION 8 PHOTOGRAPHS




Photo No. 1



Photo No. 2

TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020



Photo No. 3



Photo No. 4



Total Quality. Assured.

16015 Shady Falls
Elmendorf, Texas 78112

Telephone: 210-635-8100
Facsimile: 210-635-8101
www.intertek.com/building

TEST SUMMARY FOR ROYSONS CORPORATION

Project No.: 104318997SAT-001

Date: 05/18/2020

SECTION 10 REVISION LOG

REVISION #	DATE	PAGES	REVISION
0	05/18/2020	N/A	Original Report Issue