Dreamscape TYPE III, 35oz, High-Impact Technical Sheet v:120123



				DREAM IT., PRINT IT., HANG IT.,	
Product Name:	DreamScape <u>High-Impact</u> ^T	м 35oz/ly (793g/m	²)		
Description:	Digitally printable Type III wallcovering with exceptional durability, and high impact resistance.				
Construction:	Embossed vinyl face with laminated fabric backing. Backing is poly-cotton woven.				
Packaging:	3" core, wound print side out, wrapped in plastic bag, shipped in heavy duty cardboard tube with end caps for protection				
Application:	Standard commercial wallcovering pastes/primers and techniques. For indoor use in environmentally controlled spaces.				
Physicals:	Various Textured Surfaces				
Print Ink(s):	Solvent, eco-solvent, UV curable, UV Gel and HP Latex				
Availability					
Availability:			US	Metric	
	D H (1	Widths:	54"	1.37m	
	Roll Sizes:	Lengths:	25yds, 50yds	30m, 50m	
		Trial Rolls:	27"x15'	.686m x 4.57m	
Weight & Thickness:					
			US	Metric	
		Weight:	35 oz. per lineal yard (23.3 oz. per square yard)	793g/m ²	
		Thickness: 0.	030- 0.040in. (depending on te	exture) 0.762-1.016mm	
Type III Properties:	Break Strength	Shrinkage Stain Resistance Coating Adhesion		Heat Aging Crocking	
Impact Resistance:	ASTM D-5420 Gardner Method - passed with 74.22 in-Ib				
Environmental:		No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen, No Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals.			
	Prop 65 compliant No	o harmful off gassing	Low VOC emitting		
Mold and Mildew Resistanc	ASTM G-21 Score of Zero @ week 3				
Air Quality:	Meets California Section IAQ 1350- Third party certified by Berkeley Analytical Associates				
Fire Testing:	Class "A" Fire Rated – tested	Class "A" Fire Rated - tested in accordance with ASTM-E84 Tunnel Test NFPA-101			
Warranty:	5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at: <u>http://www.dreamscapewalls.com/</u>				